

## MODEL 405260-920 NSN: 6130-01-516-0755

Behlman's 405260-920 COTS EMDU Power Supply is a highly reliable, switch mode units built for high-end industrial or Military applications. The EMDU Supply can accept a three phase 115/200 VAC, 400 Hz input and can supply eight DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications, and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Unit is air cooled.

**INPUT** Input Transient protection per Mil-STD-704A  
115/200 VAC +/- 20%, 360-440 Hz

### OUTPUT:

1. +5 VDC @ 45 A
2. -5.2 VDC @ 6 A
3. -2 VDC @ 1.5 A
4. +6.3 VDC @ 0.5 A
5. +15 VDC @ 5 A
6. -15 VDC @ 4 A
7. +28 VDC @ 4.5 A

**Load Regulation:** 1.0% no load to full load at nominal line.

**Line Regulation:** 0.1% for 10% line change.

**PARD-Ripple & Noise:** 1% of output voltage p-p maximum. (0.1-10 MHz bandwidth)

**Over voltage protection:** 130% max.

**Short circuit protection:** Included

**Current Limit:** Constant current limited to 130% of rated current max.

**Efficiency:** 75%.



### GENERAL CHARACTERISTICS

#### Isolation

**Input to Output:** 1000 VDC

**Input to Case:** 1000 VDC

**Output to Case:** 200 VDC

**Dimensional Data:** 11.5"L X 8.75"W X 4.0"H

**Weight:** 13.5 lbs

**Input:** M24308/4-1W

**Output:** M24308/6-15

### ENVIRONMENTAL:

**Operating Temperature:** -40°C to 90°C case temperature

**Storage Temperature:** -57°C to 85°C

**MTBF** 90,000 @ 25 Degrees C base plate, Ground benign

#### Designed to meet the following MIL Standards

**Shock:** MIL-S-901; MIL-STD-810C

**Vibration:** MIL-STD-167; MIL-STD-810C; RTCA/DO-160

**Humidity:** MIL-STD-810C

**EMI/EMC:** MIL-STD-461C/D; RTCA/DO-160. RE102 with proper shielding.

**Input power:** MIL-STD-704A

Headquarters  
80 Cabot Court Hauppauge, NY 11788  
(631) 435-0410 (800)874-6727 Fax(631)951-4341

**BEHLMAN**

e-mail: sales@behlman.com  
Web-site: www.behlman.com

West Coast Office  
2363 Teller Rd, Suite 108, Newbury Park, CA 91320  
(805)375-7046 (800)456-2006 Fax(805)498-2147