

## DCS2000D -1- ( 5,120)-(3.3,160) P/N 94038

Behlman's DCS2000 series of COTS power supplies are low cost, highly reliable, switch mode units built for high-end industrial or MIL applications. The DCS2000 can accept a wide range of inputs and can supply a variety of DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications and designed to meet the input power requirements of MIL-STD-704 and MIL-STD-1399. Units are Base Plate cooled.

**INPUT**            Input Transient protection: Per Mil-STD-1399  
-1:                85-265 VAC, 47-440 Hz, Power Factor Corrected

### OUTPUT (S):    D (Dual)

Voltage/Current	5 VDC +/-1% @120 A 3.3 VDC @ 160 A
Load Regulation:	0.2% Maximum (0-100%)
Line Regulation:	0.2% Maximum
PAR-D-Ripple & Noise:	1% Typical
Current Limit:	Short Circuit and Over Current Protected
Over voltage:	Included
Efficiency:	77% Typical
Remote Sense:	0.6V compliance

### GENERAL CHARACTERISTICS- See O&C drawing 24112

Isolation	
Input to Output:	1000 VDC
Input to Case:	2500 VDC
Output to Case:	200 VDC
Dimensional Data:	14"L X 8.0"W X 2.0"H
Weight:	5.6 lbs
J1- Input:	7W2 Type Positronics
J2- Output:	8W8 Type Positronics
J3- Output:	13W6 Type Positronics

### ENVIRONMENTAL:

Operating Temperature:	-40 to +85 degrees C Base Plate
Storage Temperature:	-40 to + 100 degrees C
Designed to meet:	
Shock:	MIL-S-901; MIL-STD-810
Vibration:	MIL-STD-167; MIL-STD-810
Humidity:	MIL-STD-810
EMI/EMC:	MIL-STD-461C/D RE02/102 compliance when installed in shielded enclosure

Headquarters  
80 Cabot Court Hauppauge, NY 11788  
(631) 435-0410 (800)874-6727 Fax(631)951-4341

**BEHLMAN**  
e-mail: sales@behlman.com  
Web-site: www.behlman.com

West Coast Office  
2362 Teller Road Suite 108 Newbury Park, CA 91320  
(805)375-7046 (800)456-2006 Fax(805)498-2147