

### BL3100-(Input)-RR-(V/F) Railroad Signal Source SPECIFICATIONS

Behlman's RR series of Railroad Signal Sources/Frequency Converters are low cost, highly reliable, switch mode units built for Railroad Signaling. The RR series can be supplied with any single or three-phase input and outputs a clean, regulated AC at a precise frequency from 25 Hz to 250 Hz. These rugged signal sources are built to support the rigors of operating in the harsh environment of Railroad signaling equipment.

#### FEATURES

- Input & Output Isolation Transformers
- Short circuit protection with Auto-reset
- Rugged construction
- Optional Alarm contacts and LED indicators
- Optional AAR terminals for input & output



#### INPUT

Voltage

**C8:** 120 VAC +/- 10%, Single-phase

**C9:** 230 VAC +/- 10%, Single-phase

**C10:** 480 VAC +/- 10%, Single-phase

Frequency: 57 - 63 Hz. Other frequency available, contact factory.

#### OUTPUT

Voltage:

Any Fixed voltage 100 to 480 VAC, single-phase,  
**Transformer Isolated and Floating.**

Frequency: Any Fixed Frequency from 50 to 250 Hz +/- 0.25 Hz

Power: 3000 VA

Current Crest Factor: 3:1

Power Factor: 100% of rated output into any power factor load

Distortion: 2.0% Typical THD, full resistive load.

Load Regulation: ±1.0% No Load to Full Load

Line Regulation: ±0.5% for ±10% Line Change

Efficiency: 80% typical

#### CONTROL CIRCUIT

External Sync:

Synchronize AC output with 120 VAC external input.

#### PROTECTIVE CIRCUITS / INDICATORS

## Inverter

Input:	Main circuit breaker and surge arrestors.
Constant Current Mode:	Overload automatically causes voltage fold-back to provide maximum current without distorting output waveform.
Overload Protection:	Short Circuit overload electronically disables output to protect load. <b>Automatic reset upon overload removal.</b>
Thermal Protection:	Internal temperature sensor prevents heat damage.
Output:	Surge arrestors & transformer isolated.
Meters:	Digital Meters for Volts, Amps & Frequency Accuracy, +/- 2% Full Scale / +/- 1 digit.

### MECHANICAL SPECIFICATIONS

Dimensions:	Two high strength 19" rack mount chassis, each: 7.0"H x 22"D.
Weight:	225 lbs
Operating Temperature:	0 to 50° C.
Cooling:	Internal fans.
Input connections:	Screw type terminals.
Output connections:	Screw type terminals.
Sync connections:	Screw type terminals

### OPTIONS:

- A: Alarms**, Contact closure & Indicator
1. Inv OK - Loss of Inverter output.
  2. Sync - Loss of sync input
  3. Lock - Out of phase condition between Inverter output and Sync Input
  4. Over Temp - Over Temperature

**AAR: AAR Terminals**, input and output

**ID: Input Turn on Delay**

**21-00:** High strength **Rack Cabinet** with casters 30"H x 31.6"D x 22.1"W.

### Model Selection:

#### **BL3100-C8-RR120/100-A-AAR**

Input: 120 VAC, single-phase  
Output: 120 VAC, 100 Hz  
Option: Alarms & AAR terminals



[www.behlman.com](http://www.behlman.com)



Headquarters:  
80 Cabot Court, Hauppauge, NY 11788  
631 435-0410 800 874-6727  
Fax: 631 951-4341

2363 Teller Road, Suite 108  
Newbury Park, CA 91320  
805 375-7046 800 456-2006  
Fax: 805 498-2147

[sales@behlman.com](mailto:sales@behlman.com)

