

### SCI-890Q-2 Power Supply

**P/N 94048 (Nominal 120VAC, Single phase)**

**P/N 94048-1 (Nominal 230VAC, Single phase)**

The SSCI-890 Power Supply is an N+1 redundant, current sharing, hot-swappable AC to DC power supply. It is a COTS Modular Design with user replaceable LRUs. The power supply has On/Off Circuit Breakers mounted on the front panel of each LRU. LRU Status Indicators are visible on the front panel. The Power Supply is 3U high (EIA standard) and 19" Rack Mountable with provisions for slide mounting. The power supply and I/O connections are shown on Outline drawing 25077. In this configuration, there are two LRU power units mounted in the left and right slots. The center LRU is a controller unit.

The power units are identical, each capable of supplying full system power. These units have front panel LED's which give LRU status. A supply can be replaced with power "on". The other LRU will continue to support full system operation. It is recommended, but not required, that the circuit breaker of the LRU to be replaced be turned off before removal. Front panel insertion – ejection handles are provided for easy installation or removal of the supplies.

The center LRU is the system controller. This unit monitors the input line and the composite DC outputs. If there is a line problem or a DC output problem, the system will not operate properly. This unit also contains a battery charger and timing control to support system shutdown during brownout conditions. There are two input control potentiometers which allow adjustment of the input line detection circuit. One adjustment varies the level at which a brownout will be detected and the other adjusts the time the anomaly must last to be detected. If an error is detected, a relay closure is sent to the computer.

### FEATURES

- N+1 redundant
- Hot swappable
- Modular design with user replaceable LRU's
- Front panel status indicators
- Rack mountable with option for slides



### SPECIFICATIONS

#### INPUT

Voltage		120 VAC, Single Phase (Nominal)
	-1	230VAC, Single Phase (Nominal)
Frequency		47-63 Hz
PFC Input		0.95 minimum
Harmonic Content	Designed to meet MIL-STD-1399	
Brownout ride-through		50ms. minimum

#### OUTPUT

5 Volts Logic power;	5 VDC @ 100 A; Adjustable +/-10%
5 Volt memory;	5 VDC @ 3A; Adjustable +/-10%
Dual 12 Volts;	+/-12 VDC @ 1.5A Common Ground
	All DC commons isolated from chassis ground
Power rating	551 watts
Efficiency:	65% minimum (75% typical) @ full load

Ripple:	100mv peak to peak for 5 VDC Outputs, 200mv peak to peak for other voltages measured at 25MHz bandwidth over temperature range.	Over current protection:	Short Circuit and Over Current Protected
Current sharing:	Automatic	Over voltage protection:	105-130% of nominal voltage
	Current limiting: voltage (auto recovery)	Current limiting:	115% minimum of rated current @ nominal
	Load regulation:	Load regulation:	1% maximum (0.5% typical) per output
	Line regulation:	Line regulation:	0.5% maximum (0.2% typical) per output

## STATUS INDICATORS

Controller LRU:	AC OK, DC OK
Power LRU:	AC OK, DC OK, FAN OK

## PHYSICAL

Dimensions:	19" Rack Mount Chassis, (3U) 5 ¼"H x 19.5"D
Weight:	42 lbs
Cooling:	Internal fans. Intake front and exhaust rear.
Slide mounting pattern:	Compatible with Standard Precision (formerly Accuride) P/N 3307-22
Test Points	All DC Outputs on Controller Front Panel
Adjustments	+5V Logic; +5V Memory; +10%, -5%
Battery	12V 7AH (on rear)

Power Connections:	(J1 to J6,) 5V Output, 9 pin (J7) Local Battery, 2 pin (J8) External Control, 12 pin (J9) Local Control, 9 pin (J10, J11) Power Fail, 4 pin (J12, J13) Memory Output, 6 pin (J14 to J16) +/- 12Volt Output, 8 pin
--------------------	---

## ENVIRONMENTAL

Operating Temperature	0°C to 45°C
Storage Temperature	-40°C to 60°C
Humidity	0% to 95% Non-Condensing

**Note: Unit designed to meet MIL-STD-1399 and MIL-STD-461**



[www.behlman.com](http://www.behlman.com)

**ORBIT POWER GROUP**  
**Behlman Electronics**

Headquarters:  
80 Cabot Court, Hauppauge, NY 11788  
631 435-0410 800 874-6727  
Fax: 631 951-4341

2363 Teller Road, Suite 108  
Newbury Park, CA 91320  
805 375-7046 800 456-2006  
Fax: 805 498-2147

[sales@behlman.com](mailto:sales@behlman.com)

