

BL15000C-1-L-5680 Current Source SPECIFICATIONS

SPECIFICATIONS

INPUT POWER

Voltage: 120/208 Vac, $\pm 10\%$, 3 ϕ

Frequency: 47-63 Hz.

OUTPUT POWER

Current: 0 to 1200 Aac, 1 ϕ

Voltage: 0-12.0 Vac, 1 ϕ

Frequency: 45 - 500 Hz

Maximum Power: 15KVA

Maximum Voltage: 12.0V

Power Factor: 100% of rated output into any power factor load.

Distortion: 1.5% maximum THD (measured at 2000 A, 50 Hz).

Current Regulation: $\pm 2.0\%$ from no load to full load.

Line Regulation: $\pm 0.1\%$ for $\pm 10\%$ of line change.

Efficiency: 85-90%

MECHANICAL

Dimensions: 30.3 in. high, 32.7 in. deep, 24.2 in. wide.

Weight: Approx. 800 lbs.

Operating Temperature: 0°C to 55°C (32°F to 131°F).



Headquarters

80 Cabot Court, Hauppauge, NY 11788
(631) 435-0410 (800) 874-6727 Fax (631)951-4341

BEHLMAN

e-mail: sales@behlman.com
Web-site: www.behlman.com

West Coast Office

2363 Teller Road Suite 108, Newbury Park, CA 91320
(805) 375-7046 (800) 456-2006 Fax (805) 498-2147

