Behlman Power Products

Inverter



SQ300-12- 60 SQ300-12- 100 SQ300-12- 250

FEATURES

- SHELF OR PLUG-BOARD MOUNT
- HIGH OVERLOAD CAPACITY
- BUILT-IN SURGE PROTECTION
- CONSTANT FREQUENCY
- CONFORMS TO AAR RECOMMENDED PRACTICES

DC - AC SQUARE WAVE INVERTER FOR RAILROAD AND TRANSIT

Behlman's SQ300 Series is a rugged inverter that supplies 120 VAC from a 12 VDC source for continuous operation or standby operation of railroad signal equipment.

The input is from a nominal 13.2 V lead acid or nickel cadmium battery, which should have a low internal impedance. The output is a square wave with a fixed frequency, 60 Hz, 100 Hz or 250 Hz, +/- 1% regardless of load, input voltage or temperature.

The output voltage is proportional to the input voltage and the inverter has a high overload capacity of 110%. The SQ300 can be shelf mounted on supplied rubber feet or plug board mounted with optional bracket.

The inverters are designed to meet the rugged mechanical and environmental requirements of railroad and transit use.

INPUT

Voltage:

12 VDC +/- 20%, approximately 30 amps (nominal 13.2 V battery)

OUTPUT

Power: 300 VA Waveform: Square wave

Voltage: 120 VAC +/- 5% isolated

and floating. Proportional

To input voltage.

Current: 2.5 Amps Overload: 110%

Frequency: Constant Frequency +/- 1%

-60 60 Hz -100 100 Hz -250 250 Hz

Efficiency: 90% typical at full load

PROTECTIVE CIRCUITS

Input: Fuse with surge arrestor

and lightning protection

Overload: Overload fault current

electronically limited to protect load... power restored when overload is

removed

Thermal: Internal temperature

sensor shuts off output to prevent heat damage

MECHANICAL & ENVIRONMENTAL

Dimensions: High-strength shelf-mount chassis with optional plug- Output: AAR terminals on front AAR terminals on front

board mount Operating Temperature:

5"W X 8"H X 9.5"D -40° to 160° F (12.7 cm x 20.3 cm x 24.1 cm) (-40° to 71° C)

Weight: 25 lbs (11.3kgs) Humidity: Up to 95% non-condensing

OPTIONS: Contact factory for additional options

PB: Standard Plug-Board mount with two tabs at top and bottom



Shown with Option PB





www.behlman.com



Headquarters: 80 Cabot Court, Hauppauge, NY 11788 631 435-0410 800 874-6727 Fax: 631 951-4341



