

DCS1000T-1- (20, 6.25) (20, 6.25) (24, 16.7) P/N 94039-1

Behlman's DCS1000T, P/N 94039-1, COTS power supply is a highly reliable, switch mode unit built for use onboard US Navy vessels. This unit has a PFC input IAW MIL-STD-1399, Section 300B and supplies three DC outputs.

The DCS1000 series can accept a wide range of inputs and can supply a variety of DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications and designed to meet the input power requirements of MIL-STD-704 and MIL-STD-1399. Units are Base Plate cooled.

INPUT Input Transient protection: Per Mil-STD-1399, Section 300B
-1: 85-265 VAC, 47-440 Hz, Power Factor Corrected

OUTPUT (S): T (Triple)

- | | |
|----------------------|--|
| 1. | 20 VDC +/-1% @ 6.25 A |
| 2. | 20 VDC +/-1% @ 6.25 A |
| 3. | 24 VDC +/-1% @ 16.7 A |
| Load Regulation: | 0.2% Maximum (0-100%) |
| Line Regulation: | 0.2% Maximum |
| PARD-Ripple & Noise: | 1% Typical |
| Current Limit: | Short Circuit and Over Current Protected |
| Over voltage: | Included |
| Efficiency: | 80% Typical |
| Remote Sense: | 0.6V compliance |



GENERAL CHARACTERISTICS-See O&C drawing OC94039-1

Isolation
Input to Output: 1000 VDC
Input to Case: 2500 VDC
Output to Case: 200 VDC
Dimensional Data: 11.32"L X 5"W X 2.0"H
Weight: 3.4 lbs
J1- Input: 7W2 Type Positronics
J2- Output: 13W6 Type Positronics

ENVIRONMENTAL:

Operating Temperature: -40 to +85 degrees C Base Plate
Storage Temperature: -40 to + 100 degrees C
Designed to meet:
Shock: MIL-S-901; MIL-STD-810
Vibration: MIL-STD-167; MIL-STD-810
Humidity: MIL-STD-810
EMI/EMC: MIL-STD-461E; CE102, CS101, CS114, CS115, CS116, RE101 & RS103
RE102 compliance when installed in shielded enclosure



www.behlman.com

ORBIT POWER GROUP
Behlman Electronics

sales@behlman.com

Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

