

# Behlman Power Products

## COTS POWER SUPPLY

Model: DCS200 (5) - 2 - (26,0.2) - (28,2) - (9,0.5) - (9,1.5) - (12,2)  
P/N: 94024-1

Behlman's DCS200 series of COTS power supplies are low cost, highly reliable, switch mode units built for high-end industrial or MIL applications. The DCS200 can accept a wide range of inputs and can supply a variety of DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Units are Base Plate cooled.

**INPUT** Input Transient protection: Per Mil-STD-704

-2: 115Vac (92 – 150Vac) / 200Vac (180 – 250Vac) 45-440Hz  
Dual input range, single phase

**OUTPUTS:** **5 total**  
26Vdc @ 0.2A  
28Vdc @ 0.75A / 2A max  
9Vdc @ 0.2A / 0.5A max  
9Vdc @ 0.5A / 1.5A max  
12Vdc @ 0.5A / 2A max

Load Regulation: 0.2% Maximum (0-100%)  
Line Regulation: 0.2% Maximum  
PARD-Ripple & Noise: 150 mV (0-10Mhz)  
Current Limit: Short circuit and over-current protected.  
Over voltage: None  
Efficiency: Typical 68%  
Remote Sense: None

### GENERAL CHARACTERISTICS

Isolation  
Input to Output: 1000 VDC  
Input to Case: 1000 VDC  
Output to Case: 200 VDC  
Leakage: < 5uA  
Dimensional Data: 8.0"L X 5.0"W X 1.1"H  
Weight: 2.5 lbs max  
J1- Input: 9 pin connector, M24308/24-25  
J2- Output: 25 pin connector, M24308/23-27

### ENVIRONMENTAL:

Operating Temperature: -40 to +85 degrees C Base Plate  
Storage Temperature: -40 to + 100 degrees C

### Designed to meet the following MIL Standards

Shock: MIL-S-901; MIL-STD-810  
Vibration: MIL-STD-167; MIL-STD-810; RTCA/DO-160  
Humidity: MIL-STD-810  
EMI/EMC: MIL-STD-461C/D; RTCA/DO-160D. RE102 with proper shielding.



Please refer to the proper outline drawing for further detail.  
Behlman dwg # : 24039-X



[www.behlman.com](http://www.behlman.com)

**ORBIT** POWER GROUP  
**Behlman Electronics**

Headquarters:  
80 Cabot Court, Hauppauge, NY 11788  
631 435-0410 800 874-6727  
Fax: 631 951-4341

2363 Teller Road, Suite 108  
Newbury Park, CA 91320  
805 375-7046 800 456-2006  
Fax: 805 498-2147

[sales@behlman.com](mailto:sales@behlman.com)

