


HPRU1000Q-6-EC-5693 High Power Replaceable Unit (LRU)

P/N: 84074

The HPRU power supply is a ruggedly built, COTS, modular design, Line Replaceable Unit. Features include hot-swappable and current sharing, with front panel status indicators and designed to meet the stringent requirements of industrial and military applications.

Features

- Hot swappable
- Modular design for user replacement
- Front panel status indicators on front panel



SPECIFICATIONS

INPUT Input Transient protection: Per Mil-STD-704, MIL-STD-1399 and MIL-STD-1285

-6: 115/200 VAC, 3 phase, 47-440 Hz

OUTPUT(S): Q (Quad)

Voltage/Current:	(5V @ 80A), (3.3V @ 10A), (12V @ 33.3A), (-12V @ 4.2A)
Power:	883 watts
Load Regulation:	0.2% Maximum (0-100%)
Line Regulation:	0.2% Maximum
PARD-Ripple & Noise:	1% typical
Current Limit:	Short circuit and over-current protected.
Over voltage:	Included
Efficiency:	72% to 85% depending on model.
Remote Sense:	0.6V compliance

STATUS SIGNALS: All signals are open collector/open drain TTL compatible.
Fault to cause a logic state low.

DC OK
FAN OK

Over Temperature

PHYSICAL

Dimensions:		1/3 Rack Mount Chassis, (3U) 5 1/4"H x 5 1/4"W x15"D) with guide pin bushings.
Cooling:	Option: EC	External fins
Connections:		XXXX
Finish:		CARC paint

ENVIRONMENTAL

Operating Temperature	-40°C to +71°C (with derating)
Storage Temperature	-40°C to +85°C
Humidity	0% to 95% Non-Condensing

Note: Unit designed to meet:

MIL-STD-1399 MIL-STD-461
MIL-STD-704 MIL-STD-810
MIL-STD-1285



Rear View

Unit appearance can change based on Options



www.behlman.com

ORBIT POWER GROUP
Behlman Electronics

Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

2363 Teller Road, Suite 108
Newbury Park, CA 91320
805 375-7046 800 456-2006
Fax: 805 498-2147

sales@behlman.com

